

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Commissioner
US Department of Commerce
United States Patent and Trademark
Office, PCT
2011 South Clark Place Room
CP2/5C24
Arlington, VA 22202
ETATS-UNIS D'AMERIQUE
in its capacity as elected Office

Date of mailing:

04 January 2001 (04.01.01)

International application No.:

PCT/AU00/00700

Applicant's or agent's file reference:

P15641PCAU

International filing date:

22 June 2000 (22.06.00)

Priority date:

25 June 1999 (25.06.99)

Applicant:

HARMAN, Philip, Victor et al

1. The designated Office is hereby notified of its election made:



in the demand filed with the International preliminary Examining Authority on:

30 October 2000 (30.10.00)



in a notice effecting later election filed with the International Bureau on:

2. The election ☒ was



was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO
34, chemin des Colombettes
1211 Geneva 20, Switzerland

Facsimile No.: (41-22) 740.14.35

Authorized officer:

J. Zahra

Telephone No.: (41-22) 338.83.38

REC'D 10 APR 2001

PCT

Applicant's or agent's file reference p15641PCAU PVF:AJB	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416).	
International Application No. PCT/AU00/00700	International Filing Date (day/month/year) 22 June 2000	Priority Date (day/month/year) 25 June 1999
International Patent Classification (IPC) or national classification and IPC Int. Cl. ⁷ G06T 7/40		
Applicant DYNAMIC DIGITAL DEPTH RESEARCH PTY LTD et al		

1.	This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.																								
2.	This REPORT consists of a total of 3 sheets, including this cover sheet. <input type="checkbox"/> This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT). These annexes consist of a total of sheet(s).																								
3.	This report contains indications relating to the following items: <table border="0"> <tr> <td>I</td> <td><input checked="" type="checkbox"/></td> <td>Basis of the report</td> </tr> <tr> <td>II</td> <td><input type="checkbox"/></td> <td>Priority</td> </tr> <tr> <td>III</td> <td><input type="checkbox"/></td> <td>Non-establishment of opinion with regard to novelty, inventive step and industrial applicability</td> </tr> <tr> <td>IV</td> <td><input type="checkbox"/></td> <td>Lack of unity of invention</td> </tr> <tr> <td>V</td> <td><input checked="" type="checkbox"/></td> <td>Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement</td> </tr> <tr> <td>VI</td> <td><input type="checkbox"/></td> <td>Certain documents cited</td> </tr> <tr> <td>VII</td> <td><input type="checkbox"/></td> <td>Certain defects in the international application</td> </tr> <tr> <td>VIII</td> <td><input type="checkbox"/></td> <td>Certain observations on the international application</td> </tr> </table>	I	<input checked="" type="checkbox"/>	Basis of the report	II	<input type="checkbox"/>	Priority	III	<input type="checkbox"/>	Non-establishment of opinion with regard to novelty, inventive step and industrial applicability	IV	<input type="checkbox"/>	Lack of unity of invention	V	<input checked="" type="checkbox"/>	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement	VI	<input type="checkbox"/>	Certain documents cited	VII	<input type="checkbox"/>	Certain defects in the international application	VIII	<input type="checkbox"/>	Certain observations on the international application
I	<input checked="" type="checkbox"/>	Basis of the report																							
II	<input type="checkbox"/>	Priority																							
III	<input type="checkbox"/>	Non-establishment of opinion with regard to novelty, inventive step and industrial applicability																							
IV	<input type="checkbox"/>	Lack of unity of invention																							
V	<input checked="" type="checkbox"/>	Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement																							
VI	<input type="checkbox"/>	Certain documents cited																							
VII	<input type="checkbox"/>	Certain defects in the international application																							
VIII	<input type="checkbox"/>	Certain observations on the international application																							

Date of submission of the demand 30 October 2000	Date of completion of the report 30 March 2001
Name and mailing address of the IPEA/AU AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustalia.gov.au Facsimile No. (02) 6285 3929	Authorized Officer JAMES WILLIAMS Telephone No. (02) 6283 2599

I. Basis of the report

1. With regard to the elements of the international application:*
- ☒ the international application as originally filed.
- ☐ the description, pages , as originally filed,
 pages , filed with the demand,
 pages , received on with the letter of
- ☐ the claims, pages , as originally filed,
 pages , as amended (together with any statement) under Article 19,
 pages , filed with the demand,
 pages , received on with the letter of
- ☐ the drawings, pages , as originally filed,
 pages , filed with the demand,
 pages , received on with the letter of
- ☐ the sequence listing part of the description:
 pages , as originally filed
 pages , filed with the demand
 pages , received on with the letter of
2. With regard to the **language**, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.
These elements were available or furnished to this Authority in the following language which is:
- ☐ the language of a translation furnished for the purposes of international search (under Rule 23.1(b)).
- ☐ the language of publication of the international application (under Rule 48.3(b)).
- ☐ the language of the translation furnished for the purposes of international preliminary examination (under Rules 55.2 and/or 55.3).
3. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, was on the basis of the sequence listing:
- ☐ contained in the international application in written form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished
4. ☐ The amendments have resulted in the cancellation of:
- ☐ the description, pages
- ☐ the claims, Nos.
- ☐ the drawings, sheets/fig.
5. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).**

* Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report since they do not contain amendments (Rules 70.16 and 70.17).

** Any replacement sheet containing such amendments must be referred to under item 1 and annexed to this report

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**1. Statement**

Novelty (N)	Claims 1-23	YES
	Claims	NO
Inventive step (IS)	Claims 1-23	YES
	Claims	NO
Industrial applicability (IA)	Claims 1-23	YES
	Claims	NO

2. Citations and explanations (Rule 70.7)**Novelty and Inventive Step**

None of the citations, individually or in combination, discloses all of the essential features of the invention defined in Claims 1-23 especially the use of an object identifier only to define the object.

IMAGE CONVERSION AND ENCODING TECHNIQUES

FIELD OF INVENTION

The present invention is generally directed towards stereoscopic image synthesis and more particularly toward an improved method of converting two dimensional (2D) images for further encoding, transmission and decoding for the purpose of stereoscopic display.

BACKGROUND

The applicants have previously described in PCT/AU96/00820, a method of producing left and right eye images for a stereoscopic display from an original 2D image including the steps of:

- a.) identifying at least one object within the original image;
- b.) outlining each object;
- c.) defining a depth characteristic for each object; and
- d.) respectively displacing selected areas of each object by a determined amount in a lateral direction as a function of the depth characteristic of each object, to form two stretched images for viewing by the left and right eyes of the viewer.

These steps can be individually and collectively referred to as Dynamic Depth Cuing or DDC.

Additionally, the Applicants have previously described in PCT/AU98/0155, in one aspect a method of encoding a depth map including the steps of:

- a.) allocating an object number to an object;
- b.) allocating the object with a depth; and
- c.) defining the object outline

The object or object outline can be defined by a series of co-ordinates, and/or curves, and in particular bezier curves where found to produce desirable results. This system could also be assisted through the use of generic libraries, both in the identification of objects within an image and also the allocation of depth of each object.

Further, the Applicants disclosed a method of transmission of the depth map information whereby the information was included in the vertical Blanking Interval or MPEG data stream.

The Applicants' prior developments enabled an operator to simply outline an object and assign a depth to that object. This information was then processed to determine the amount of stretching required in order to place the object at the assigned depth. From an end user point of view this system is intuitive and allows the user to interactively alter the depth of an object to obtain an artistically pleasing result. From a processing point of view, the use of Bezier curves proves a highly efficient means of compressing the necessary data. However, whilst the use of Bezier curves is an efficient compressing technique, it is a relatively complex system to implement. Accordingly, a simplified technique of generating and processing depth maps is desired.

OBJECTIVE OF INVENTION

It is an objective of the present invention to provide a relatively simple technique of generating and processing depth maps, and further improve the operations of the Applicants earlier image conversion and encoding techniques.

SUMMARY OF INVENTION

With the above objectives in mind, the present invention provides in one aspect a method of encoding a depth map including:

- identifying and outlining an object within an image;
- allocating an object identification symbol to the object;
- using the allocated object symbol to represent the shape of the object; and
- allocating the object with a depth.

Advantageously, the present invention will include the further steps of:

- compressing the information representing the object and its depth;
- transmitting and/or storing the compressed information; and
- decompressing the information.

In another aspect the present invention provides a method of encoding a depth map including:

- identifying and outlining an object within an image;
- allocating an object identification symbol to the object;
- defining the object by drawing a plurality of lines across the image, and determining the start and finish positions of each said line, wherein a new line is commenced each time an object boundary is reached;

allocating the object with a depth;

Preferably, the said lines will extend horizontally across the screen. However, it will be appreciated that the lines could equally extend vertically across (or up and down) the screen.

5 BRIEF DESCRIPTION OF THE DRAWINGS

To provide a better understanding of the present invention, reference is made to the accompanying drawings which illustrate a preferred embodiment of the present invention.

IN THE DRAWINGS:

10 Figure 1 shows a group of objects that have been identified, as previously disclosed and allocated a number.

Figure 2 shows how the shape of each identified object may be defined using the object number defined in Figure 1.

Figure 3 shows how the information representing this group of objects can
15 be compressed.

Figure 4 shows an alternative method for representing each object and its depth.

DETAILED DESCRIPTION OF INVENTION

In the preferred embodiment, the image conversion technique includes the
20 following steps:

OBJECT IDENTIFICATION

Objects in the 2D image to be converted may be identified using any of the methods previously disclosed in application PCT/AU98/01005, the contents of which are hereby included herein by reference. For illustrative purposes only,
25 assume that the image to be converted is as per Figure 1. This image consists of four objects, namely a disk which has been allocated object number 1, a triangle that has been allocated object number 2, a square that has been allocated object number 3 and the background that has been allocated object number 4. It will be understood that the objects need not be allocated numerals, and that alphanumeric
30 characters or any other symbol could also be used.

OBJECT REPRESENTATION

As shown in Figure 2 the shape of each of these objects within the image may be defined by using each object identification symbol, in this case a number, to "paint" the shape of the object. Alternatively, it can be considered that the object is "filled" with the object identification symbol. In either event the shape of the object may still be determined such that a user or viewer may still be able to identify the painted object.

As can be seen from Figure 2, object 1 has been reproduced using the symbol 1, object 2 the symbol 2, object 3 the symbol 3 and object 4 the symbol 4.

10 OBJECT COMPRESSION

In order to efficiently store or transmit the information representing the objects shown in Figure 1 it is necessary to compress the information. The compression and decompression process should be able to be undertaken both in software and/or hardware and operate in a fast and efficient manner.

15 In the case of the 2D to 3D conversion of video, where the object information is included in the Vertical Blanking Interval or MPEG stream, it is desirable that the decompression should operate sufficiently rapidly to enable real time 2D to 3D conversion of the associated 2D image.

A simple compression technique is to run length encode for each line of Figure 2. This is shown in Figure 3. The first line of Figure 2 consists of the symbol 4 repeated 50 times. Using run length encoding this would compress to
4(50)

which indicates that the symbol 4 is to be repeated 50 times along that line.

In a similar manner, each line of Figure 2 is processed to produce Figure 3.

25 To decompress Figure 3 the reverse process is applied.

This compression technique can effectively reduce the data required to represent Figure 1 to 20% of its uncompressed value. If desired, additional compression may be applied.

It will be appreciated by those skilled in the art that many other data
30 compression techniques are suitable for this application. This would include, although not limited to, Lenple Ziv, Huffman and Shannon-Fano.

Once an object has been defined using the above process a differential encoding technique can be used to eliminate the need to transfer or store data that is consistent in consecutive images. The differentially encoded data can then be compressed as previously described.

5 DEPTH MAPS

As previously disclosed, in order to use this representation of an object to form a depth map each object needs to be allocated a depth. The manner of defining the depth of an object is as previously disclosed in PCT/AU98/01005. Therefore, each object identified in Figure 1 will have associated with it a depth identifier in the form:

<object number> <depth flag> <depth operator>

Where <depth flag> indicates the type of depth information that follows and <depth operator> are any parameters associated with the specific type of depth flag.

15 This object depth information may be added to the object data stream either before or after compression.

In an alternative embodiment, the image conversion technique includes the following steps:

OBJECT IDENTIFICATION

20 Objects in the 2D image to be converted to 3D are identified as previously described. For purposes of explanation we will use the objects identified in Figure 1.

OBJECT REPRESENTATION

The shape of each object can be represented by drawing a series of
25 horizontal lines across the image such that a new line is started each time an object boundary is crossed. This is illustrated in Figure 4.

The x, y co-ordinates of the starting point of the first line, marked Z1 in Figure 4 will be known and for illustrative purposes will be assigned 0,0. Likewise the end point of the line, marked Z2 in Figure 4, will be known and for illustrative
30 purposes will be assigned 0,255.

Lines (Z1,Z2) (Z3,Z4) Z5,Z6) represent the first few lines of object 4. The values of Zn indicate the depth at which the object is to appear in the final

stereoscopic image. For illustrative purposes we will assume that there are 255 possible depth values, such that depth 0 is closest to the viewer and depth 255 farthest from the viewer.

If, for example, object 4 is to appear at a constant depth 100 from the viewer
5 then the values of Z1 and Z2 would be 100.

If, however, it was desired that object 4 should appear to ramp away from the viewer then Z1 could be set to 50 and Z2 to 100. The 2D to 3D conversion process previously disclosed in PCT/AU98/01005 would then interpolate the depth data and produce the appropriate 3D images.

10 Conversely, should it be desired that object 4 should appear to both ramp away from the viewer and tilt away then Z_{n-1} could be set to 75 and Z_n set to 100.

Referring to Figure 4, the line identified as starting at Z7 would therefore consist of 3 segments as follows:

- Z7 to Z8 - which defines the segment of object 4;
- 15 Z9 to Z10 - which defines the segment of object 3;
- Z11 to Z12 - which defines the segment of object 4

Whilst the x, y location of points Z1 to Z7 and Z12 will be known, since they border the image, the location of points Z8 to Z11 are determined by the size of the objects being described, and can be determined from the outline of the object(s).

20 The allocation of depths Z_a and Z_b will allow a linear depth ramp to be applied to an object. However, since it is desirable to add other than linear ramps to an object, for example radial ramps, the centre of the radial ramp (x, y) and its radius (z) will also need to be known.

Thus the general format for a line describing both an objects length and
25 assigned depth is

start_depth, end_depth (length, centre (x, y), radius)

Where start_depth is relative to either the left hand edge of the image or the previous object identification and length, centre and radius may be required depending upon the length of the line (i.e. if the length is not equal to the image
30 width) and assigned depth characteristics.

For example, using start_depths relative to the previous object, and assuming a 0 to 255 by 1 to 255 image with object 4 at a constant depth 50 and

object 3 at a constant depth 20, and assuming that object 3 runs from co-ordinate (76,4) to (200,4), the data for the first 4 lines of Figure 4 will be:

	Line 1	50
	Line 2	50
5	Line 3	50
	Line 4	50, 50, 75 20, 20 125 50, 50, 55

This data can be compressed as previously described or using other compression techniques familiar to those skilled in the art. Similarly, the allocation of a depth for each object is as previously disclosed.

10 ALTERNATIVE PROCESS FOR DEPTH ASSIGNMENT

An alternative method of assigning the depth of an object is to "paint" the object using a graphics paint brush or air brush, such as used in the Adobe Photoshop graphics software, with a colour equal to the depth that is to be assigned to the object.

15 For illustrative purposes assume that there are 256 different depth levels available with 0 representing an object closest to the observer and 255 furthest away from the observer. Assume that depth 0 is assigned to white and 255 to black then intermediate depths will be assigned a shade of grey.

Considering Figure 1, assume that object 1 is to be set to depth 10. The
20 operator selects depth 10 from a pallet which determines a corresponding shade of grey to assign to the graphics paint brush or air brush.

The operator then paints the area of object 1 with the brush, thus allocating depth 10 to the object. Since the operator can see the results of his actions on the computer screen it is possible to accurately select objects.

25 Different size brushes, or air brush patterns, may be selected to allow fine detail or rapid fill of large areas. Errors can be corrected using a graphical eraser such as found, for example, in Adobe Photoshop.

Once the shape of an object has been painted using the brush the depth of the object can be altered if necessary by altering the shade of grey. Standard
30 techniques such as found in graphics drawing packages can be used to change the shade of grey.

Using a mouse, or other locating device, it is possible to add variations in object depth within an object. The variations in depth are applied by selectively changing the shade of grey within the object. Examples of the depth variations include, but are not limited to, linear ramps, non-linear ramps and radial ramps.

- 5 Painting the object with a shade of grey has been chosen for illustrative purposes only. In practice any colour, shape or symbol may be used to enable the operator to paint the selected object.

A preferred embodiment includes separating the steps of painting the object and selecting the depth of the object. An effective process is to cause the object
10 being painted to take on transparent or glass like texture. This enables the operator to see areas of the object that have already been painted rather than obscuring them with a solid colour. Once the object has been painted in this manner a solid depth colour can be applied.

ALTERNATIVE PROCESS FOR CREATING BEZIER CURVES

- 15 Since the peripheral edges of the object are known it is possible to locate the boundary of the object and automatically construct Bezier curves that trace the peripheral of the object. The Bezier curves may be adjusted as necessary to cause exact alignment of the object and also adjusted to allow for movement of the object as it moves in successive frames.

20 ALTERNATIVE PROCESS FOR TRANSPORT OF DDC DATA

In previous applications, it has been assumed that the Dynamic Depth Cueing (DDC) data has been imbedded in the original 2D image in either the Vertical Blanking Interval or MPEG stream.

- In practice this is a convenient way to transport and store the DDC encoded
25 2D images. However, it will be understood by those skilled in the art that the DDC data and original 2D images can be stored and transported separately if desired.

For example, if the original 2D image were a video sequence that was held on a data server accessible via the Internet then the DDC data could be accessed
30 from the same server or an entirely different server in a geographically different location. The user could then download the video sequence and DDC data relating

to the video sequence independently and combine them either at the time of viewing or prior to viewing.

The application of the DDC data to the original video sequence to create 3D can be undertaken in real time, as the viewer looks at the images, or off-line prior to
5 viewing. The creation of 3D from the DDC data and the original 2D image can be undertaken in either software or hardware as previously disclosed.

In relation to software conversion from 2D to 3D, a convenient way to achieve this on a Personal Computer (PC) is to provide a software plug-in for an existing 2D viewer. For example, a plug in for the Apple QuickTime movie viewer
10 would be suitable for general PC viewing as would plug-ins for Internet Web browser such as Internet Explorer and Netscape Communicator. These plug-ins could be most conveniently provided to the viewer by downloading over the Internet.

Alternatively a custom software application could be developed and
15 conveniently provided to the user via a download from the Internet or other efficient method.

USE OF DDC FOR THE 2D TO 3D CONVERSION OF STILL IMAGES

A subset of the use of DDC data for the conversion of 2D moving images into 3D is the conversion of still images. The original image may be in any digital
20 format and may have originated from either a film camera, with the resulting image being scanned to produce a digital file, or directly from a digital still or moving camera.

For transfer between Personal Computers and in particular transfer over the Internet, it is desirable that the DDC data is imbedded in a standard image format.
25 Such formats are known to those skilled in the art and include, but are not limited to, JPEG, BMP, GIFF and TIFF.

JPEG and GIFF are compressed formats that also enable the insertion of private data within the image files. In a preferred embodiment the DDC data is included in the private data area of these compressed image formats.

30 This process therefore enables an image containing DDC data to be viewed in either 2D, if the user does not have either a suitable viewer or plug-in, or 3D if a viewer or plug-in is available.

As previously disclosed, DDC data may be used to create both a stereo pair of images and also a number of stereo pairs suitable for use with autostereoscopic displays using lenticular lenses. An example of such a display is that manufactured by Philips which requires 7 or 9 pairs of stereo images.

5 For use with a still image, the DDC data can be used to produce multiple monoscopic or stereoscopic views from an original 2D image. In a preferred embodiment such images could be viewed on a Personal Computer using a Windows interface with the viewpoint selected by moving a horizontal slider bar.

10 Whilst the method and system of the present invention has been summarised and explained by illustrative examples, it will be appreciated by those skilled in the art that many widely varying embodiments and applications are within the teaching and scope of the present invention, and that the examples presented herein are by way of illustration only and should not be construed as limiting the scope of this invention.

15

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A method of encoding a depth map including:
identifying and outlining an object within an image;
allocating an object identification symbol to said object;
using the allocated object symbol to represent the shape of said object; and
allocating said object with a depth.
2. A method as claimed in claim 1 wherein said object identification symbol is an alphanumeric character.
3. A method as claimed in claim 1 wherein said object identification symbol is a symbol.
4. A method as claimed in any one of the preceding claims wherein said object is filled with said object identification symbol.
5. A method as claimed in any preceding claim further including the step of:
compressing the information representing said object and its depth.
6. A method as claimed in claim 5 further including the steps of:
transmitting and/or storing said compressed information; and
decompressing said compressed information.
7. A method as claimed in claim 5 or 6 wherein said decompressing of the information is in real time.
8. A method as claimed in any one of claims 5 to 7 wherein said step of compressing the information uses run length encode for each line of said image.

9. A method as used in any one of claims 5 to 7 wherein each line of said image is compressed by representing the information in the following format:

A(X)...

wherein A represents the object identification symbol, and X represents the number of consecutive pixels that A covers.

10. A method as claimed in any one of claims 5 to 9 wherein said compressed information is further compressed.

11. A method as claimed in claim 10 wherein said further compression uses Lenple Ziv, Huffman or Shannon-Fano techniques.

12. A method as claimed in any preceding claim further including the step of: assigning each said object a depth identifier.

13. A method as claimed in claim 12 wherein said depth identifier is of the form:
<object number> <depth flag> <depth operator>
wherein object number is the number allocated to the object, depth flag indicates the type of depth information, and depth operator are parameters associated with said depth information.

14. A method of encoding a depth map including the steps of:
identifying and outlining an object within an image;
allocating an object identification symbol to said object;
defining said object by drawing a plurality of lines across said image, and determining the start and finish positions of each said line, wherein a new line is commenced each time an object boundary is reached; and
allocating said object with a depth;

15. A method as claimed in claim 14, wherein said lines extend horizontally across said screen.

16. A method as claimed in claim 14, wherein said lines extend vertically down said screen.

17. A method as claimed in any one of claims 14 to 16 wherein each said line is defined in the following format:

$A, B(x)$

wherein A is the depth at the start of the line, B is the depth at the end of the line, and x is the length of the line.

18. A method as claimed in any one of claims 14 to 16 wherein each said line is defined in the following format:

$A, B(x, C(y, z), r)$

wherein A is the depth at the start of the line, B is the depth at the end of the line, x is the length of the line, $C(y, z)$ is the centre point of a radial ramp, and r is the radius of said radial ramp.

19. A method as claimed in any preceding claim wherein said objects are painted a colour by an operator to assign a depth to said object, said colour being predefined for a certain depth.

20. A method as claimed in claim 19 wherein the colour assigned by said operator is a shade of grey ranging from white to black.

21. A method as claimed in any one of claims 1 to 18 wherein said objects are painted a colour by an operator, and then said colour is assigned a depth value.

22. A method as claimed in any preceding claim wherein said depth map is attached to or embedded in said image.

23. A method or system substantially as hereinbefore described with reference to the accompanying drawings.

Fig 1.





Fig 2.




2/2

Fig 3

2(50)					
2(50)					
2(50)					
2(50)					
2(50)					
2(10)	3(28)	4(12)			
2(10)	3(28)	4(12)			
2(10)	3(10)	2(1)	1(7)	3(5)	4(12)
2(10)	3(9)	2(2)	1(11)	3(3)	4(12)
2(10)	3(7)	2(3)	1(14)	3(3)	4(12)
2(10)	3(6)	2(4)	1(16)	3(1)	4(12)
2(10)	3(5)	2(6)	1(14)	3(2)	4(12)
2(10)	3(3)	2(8)	1(11)	3(3)	4(12)
2(10)	3(2)	2(11)	1(7)	3(3)	4(12)
2(11)	2(20)	4(19)			
2(10)	2(22)	4(18)			
2(9)	2(24)	4(17)			
2(50)					
2(50)					

Fig 4.



INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU00/00700

A. CLASSIFICATION OF SUBJECT MATTER

Int. Cl. ⁷: G06T 7/40

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: GLOBAL

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
INTERNET

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPAT: depth map

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
	WO 99/30280 (DYNAMIC DIGITAL DEPTH RESEARCH PTY LTD) 17 June 1999	
X	whole document	1-13
A	whole document	14-23
	US 5,793,900 (Nourbakhsh et al) 11 August 1998	
X	whole document	1-13
A	whole document	14-23
	US 4,947,347 (Sato) 7 August 1990	
A	whole document	1-23

☐ Further documents are listed in the continuation of Box C ☒ See patent family annex

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier application or patent but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"&" document member of the same patent family

Date of the actual completion of the international search
25 July 2000

Date of mailing of the international search report
- 7 AUG 2000

Name and mailing address of the ISA/AU
AUSTRALIAN PATENT OFFICE
PO BOX 200, WODEN ACT 2606, AUSTRALIA
E-mail address: pct@ipaustalia.gov.au
Facsimile No. (02) 6285 3929

Authorized officer
JAMES WILLIAMS
Telephone No : (02) 6283 2599

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.
PCT/AU00/00700

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report				Patent Family Member	
US	4947347	DE	3831428	JP	1076374
END OF ANNEX					